



Lyden Oil Company

ProGuard

Product Information

ProGuard L-Plex Grease

ProGuard L-Plex Greases are lithium complex thickened, multifunctional extreme pressure (EP) greases formulated to withstand constant temperatures up to 375° F of continuous exposure and 450° F of intermittent temperatures. It meets the NLGI GC-LB specification for use as a multipurpose wheel bearing and chassis lubricant and is dyed red for easy identification and leak detection.

ProGuard L-Plex Greases can be used for a wide range of heavy-duty, automotive, and industrial grease applications. It is available NLGI grade #2 for general purpose use, and also a softer NLGI #1 grade for better pumpability through grease distribution systems.

Applications

- Chassis lubrication on automobiles, heavy-duty trucks, agricultural and off-road equipment
- Automotive wheel bearings, disc brakes, ball and roller bearings, bushings, cams, splines, universal joints, pins, and slides
- Industrial bearings that endure slow to moderate speeds and heavy loads
- Any application that requires a premium, high temperature, extreme pressure grease.

Benefits

- Red color for easy identification
- High dropping point
- High load carrying ability
- Extreme pressure protection
- Excellent protection against rust and corrosion
- Water Resistant
- Stays in place

ProGuard L-Plex Grease

	#1	#2
Thickener	Lithium Complex	Lithium Complex
NLGI Grade	1	2
Color	Red	Red
Appearance	Smooth/Tacky	Smooth/Tacky
Dropping Point, °F, ASTM D2265	525	525
Base Oil Viscosity, cSt @ 40°C, ASTM D445	200	200
Viscosity Index, ASTM D2270	98	98
Timken OK Load, lbs., ASTM D2509	60 min.	60 min.
4-Ball EP Weld Point Test, Kg, ASTM D-2783	400	400
Rust Protection	Pass	Pass

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com