



# Lyden Oil Company

## ProGuard

### Product Information

#### **ProGuard NL1A Plus**

**ProGuard NL1A Plus** is an Extreme Pressure ISO 460 gear oil suitable for use in heavily loaded applications.

**ProGuard NL1A Plus** is primarily intended for use in open gears, chains and wire ropes. Due to the thickness of the 460 gear oil and the special tacifiers used ambient and operating temperatures must be considered for each particular applications.

**ProGuard NL1A Plus** is also recommended for flexible couplings, gears and sliding surfaces of drag lines and shovels, open gears of mine hoists, ball mills, rubber mixers, cement mills as well as other applications where a heavy, adhesive oil is required.

**ProGuard NL1A Plus** was developed specifically to give the user all benefits where water conditions are involved and where the lubricant must withstand washing action.

#### Typical Properties

#### **ProGuard NL1A Plus**

Product Code Number	61079-460
NLGI Grade	460
Color	Dark Brown
Viscosity, ASTM D-445 cSt at 40 °C	414-506
Viscosity Index, ASTM D-2270	95
Flash Point, °C (°F), ASTM D-92	227 (440)
API Gravity, ASTM D-287	21.6-24.6
Density, lbs/gal	7.622
Four Ball EP Weld Point, Kg, ASTM D-2596	620

#### **Lyden Oil Company**

30692 Tracy Road  
Walbridge, OH 43465  
1(800)24-LYDEN  
local: (419)666-1948  
fax: (419)666-8790  
gam@lydenoil.com

3711 LeHarms Road  
Youngstown, OH 44515  
1(800)362-9410  
local: (330)792-1100  
fax: (330)792-1462  
lal@lydenoil.com

16275 National Parkway  
Lansing, MI 48906  
1(800)968-6457  
local: (517)485-2285  
fax: (517)485-0605  
jtr@lydenoil.com

8151 Millis Road  
Shelby Township, MI 48317  
local: (586)997-1319  
fax: (586)997-1352  
jcc@lydenoil.com

3249 Wales Ave. NW  
Massillon, OH 44646  
local: (330)832-7800  
fax: (330)832-2787  
lal@lydenoil.com