



Lyden Oil Company

ProGuard

Product Information

ProGuard Sparmist V

ProGuard Sparmist V is a vegetable oil based cutting lubricant that is formulated with extreme pressure and lubricity additives. It is intended for use on all ferrous as well as aluminum metals and alloys.

Typical Properties

ProGuard Sparmist V

Product Code Number	803221
Color	Golden-Yellow
Appearance	Clear Liquid
Viscosity, ASTM D-445	
cSt at 40 °C	20-30
SUS at 100 °F	90-140
API Gravity	24.0
Specific Gravity, ASTM D-1298	0.9088
Density, lbs/gal	7.57
Sulfur	Nil
Chlorine	Nil
Phosphorus	Present

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarms Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com