



Lyden Oil Company

ProGuard Product Data

ProGuard Met-Protect

(Naphthenic Oil - Solvent Based Rust Preventative)

Product Data Sheet

ProGuard Met-Protect is solvent based corrosion inhibitor designed to be used as received to achieve long term (two years or more indoors) rust inhibitor.

ProGuard Met-Protect will leave a very light naphthenic oil film coating after the solvent carrier evaporates off. The product is ready to use or it can be cut back for a thinner protective coating for further economy in applications requiring a shorter term of corrosion protection.

ProGuard Met-Protect may be applied by spraying, dipping, wiping or swabbing. In applications where induction heat treating occurs, the Met-Protect will burn off with a light white smoke.

Typical Characteristics

Color	Amber
Odor	Typical
Appearance	Clear
Density	6.755 lb/gal
Viscosity @40 Deg C	3 – 6 cSt.

100819

Lyden Oil Company

3249 Wales Ave. NW
Massillon, OH 44646
(330)832-7800
fax: (330)832-2787

3711 LeHarms Rd.
Youngstown, OH
(800)362-9410
fax: (330)792-1462

2649 Tracy Rd.
Northwood, OH
(800)245-9336
fax: (419)666-8790

419 Spring St.
Lansing, MI 48101
(800)968-6457
fax: (517)485-0605

24200 W. Outer Dr.
Allen Park, MI 48912
(313)383-0097
fax: (313)383-2342