



Lyden Oil Company

ProGuard Product Data

ProGuard Premium Form Oil Product Data Sheet

ProGuard Premium Form Oil is blended using selected base oils and special additives designed to wet metal and wood form materials, giving excellent parting characteristics to concrete forms. Designed to meet regulation of VOC emissions from architectural coatings under Section 183 (e) of the Clean Air Act.

ProGuard Premium Form Oil is designed to keep forms clean and provide longer form life while providing rust protection to metal forms. **ProGuard Premium Form Oil** provides cleaner and easier separation of concrete from metal, wood and other forms. **ProGuard Premium Form Oil** contains special mold release agents that chemically react with the concrete which promotes easy separation from metal forms. **ProGuard Premium Form Oil** also contains a physical film barrier agent which aids in the ease of separation from the forms.

ProGuard Premium Form Oil may be brushed, sponged or sprayed on.

ProGuard Premium Form Oil has also been successfully used when sprayed on cement mixer drums to facilitate easier cleaning of the mixers.

ProGuard Premium Form Oil meets the requirements for Cleveland Architectural Grade Concrete Form Oil.

Benefits

- Clean separation from forms
- Rust protection to metal forms
- Minimized rust and corrosion
- Good low temperature pour point for indoor and outdoor use

Typical Characteristics

ProGuard Premium Form Oil	
Base Oil Viscosity	
@40 Deg. C, cSt	6.6
Flash Point (min. Deg F)	275
Lbs./gal	7.27
VOC/gms/liter	90

071101

Lyden Oil Company

3249 Wales Ave. NW
Massillon, OH 44646
(330)832-7800
fax: (330)832-2787

3711 LeHarps Rd.
Youngstown, OH
(800)362-9410
fax: (330)792-1462

2649 Tracy Rd.
Northwood, OH
(800)245-9336
fax: (419)666-8790

419 Spring St.
Lansing, MI 48101
(800)968-6457
fax: (517)485-0605

24200 W. Outer Dr.
Allen Park, MI 48912
(313)383-0097
fax: (313)383-2342